TECHNICAL DATA SHEET

Cosmedico®
FIRST CHOICE IN TANNING

Cosmolux COLYOUR YELLOW Premium R 40 180W 2M

NAFTA Code: FR79 T12 180W HO PH
Equivalency Code: 180-R-40/4,1

Item Code: 32306

Electrical data (nominal values)	
Lamp power	180 W
Supply voltage	230 V
Ballast	180 W / 230 V

Physical data	
UVA flux (315-400 nm) ±10%	33 W
UVA irradiance (315-400 nm) ±10%	20 W/m²
UVB irradiance (280-315 nm) ±10%	292 mW/m²
UVB/UVA ratio	1,5 %
Recommended useful life	800 hrs

Lamp specifications (acc. IEC/EN 61228)

a) Dimensions (in mm)	
Length (nominal)	2.000,0
Length without pins (max)	2.001,3
Length base – pin (min)	2.006,0
Length base – pin (max)	2.008,4
Length with pins (max)	2.015,5
Diameter (nominal/max)	38,0 / 40,5
Base	G13 standard

b) Reflector	210°

c) Specified ballast	Cosmopower S 180W/230V

d) Electrical data (rated values)	
Lamp power	182 W
Lamp current	1.855 mA
Lamp voltage	112 V

e) Effective irradiance (rated values)	
UV-Erythema (250-400 nm) ±15%	40 mW/m²
nmsc (250-320 mm) ±15%	58 mW/m²
nmsc (320-400 mm) ±15%	14 mW/m²

f) Equivalency code	180-R-40/4,1

Examples of exposure times

UVA irradiance	First session tanning time	Maximum tanning time in Min. by skin type		
in W/m²	*in Min.*	*2*	*3*	*4*
160	4,9	12,2	17,1	22,0
210	3,7	9,3	13,0	16,7
260	3,0	7,5	10,5	13,5
310	2,5	6,3	8,8	11,3
360	2,2	5,4	7,6	9,8

(depending on the actual UVA irradiance of the sunbed)

Construction elements	
Mount	SM
Glass type	closed
Light Colour	see picture

Equipment requirements	
Starter	180 W / 230 V
Starter $t_{close\ min}$	
Starter $t_{close\ max}$	
Starter $U_{peak\ min}$	
Starter $U_{nonrecl\ max}$	
Cathode $I_{preheat\ min}$	
Cathode $I_{preheat\ max}$	
Operating condition $U_{L\ min}$	
Operating condition $U_{L\ max}$	
Operating condition $I_{L\ min}$	
Operating condition $I_{L\ max}$	

Additional specifications

This lamp is intended for sun-tanning purposes only and shall not be used in any other application

Relative spectral distribution

